

BCR-TEKES6200

2D Hand Scanner with Stand



Image Sensor	640x480 CMOS
Ambient Light Intensity	0~100000 Lux
Reading Code System	1D Code 128, UCC/EAN-128, AIM 128, EAN-8, EAN-13, ISSN, ISBN, UPC-E, UPC-A, Interleaved 2 of 5, ITF-6, ITF-14, Matrix 2 of 5, European 25, Standard 25, Code 39, Codabar, Code 93, Code 11, Plessey, MSI-Plessey, RSS-14, RSS-Limited, RSS-Expand 2D PDF417, Data Matrix, QR, Micro QR
Typical Reading Depth of Field	QR CODE(30MIL) 0-20CM, CODE 128 (10MIL) 0-18CM
Barcode Sensitivity	Tilt $\pm 60^\circ$ @ 0° Roll and 0° Skew Rotate 360° @ 0° Pitch and 0° Skew Deflection $\pm 55^\circ$ @ 0° Roll and 0° Pitch
Lowest Contrast	$\geq 30\%$
Data Interface	USB
Reading Accuracy	$\geq 5\text{mil}$
Operating Current	1520mA \pm 15mA
Standby Current	120mA \pm 2mA
Operating Temp	-20°C~50°C
Relative Humidity	5%~95% (non-condensing)
Size	172mm x 71mm x 99mm
Weight	251.5g